



INTERIOR VENETIAN BLINDS

THE IDEAL LIGHT

BENEFITS

Interior venetian blinds control and dose the incoming daylight in a convenient way. As functional elements of the interior decoration they create individual comfort and help to control the room temperature. HELLA offers a wide range of interior venetian blinds, perfectly combinable with other shading variants.

Your HELLA benefits for this product:

- View and glare protection
- Combination of heat protection and view
- Different operating variants

| Model | min. width [mm] | | max. width [mm] | max. height [mm] | max. surface [m ²] |
|--|--------------------------|--------------------------|-----------------|------------------|--------------------------------|
| | Complete height <2000 | Complete height >2001 | | | |
| JI 25 ISOLINE chain drive | 320 | 390 | 2000 | 2500 | 2.5 |
| JI 25 ISOLINE motor drive | 590 | 730 | 3000 | 3500 | 4 |
| JI 25 ISOLINE motor drive with radio | 710 | 980 | 3000 | 3500 | 4 |
| JI 25 chain drive, chain exit at the front | 430 | 480 | 3000 | 3500 | 4 |
| JI 25 chain drive, lateral chain exit | 310 | 390 | 3000 | 3500 | 4 |
| JI 25 pull cord, cord exit at the front | 300 | 300 | 2100 | 3000 | 3 |
| JI 25 operating handle | 430 | 480 | 3000 | 3500 | 4 |
| JI 25 coupled window venetian blind pull cord | 240 | 240 | 1500 | 3000 | 3 |
| JVF 25 chain drive | 255 | 335 | 3000 | 3500 | 2.7 |
| JVF 25 motor drive * | 465/505 ** | 585/625 ** | 3000 | 3500 | 4 |
| JVF 25 motor drive with radio * | 650/690 ** | 720/760 ** | 3000 | 3500 | 4 |

ISOLINE JI 25 with cover plate (freely suspended or cable guided)

* Different minimum widths and designs upon request

** min. width with wire tensioning

Models 35 mm not shown here are available upon request!



Interior venetian blinds

Optimal control of the sunlight creates a comfortable atmosphere in the room.


TYPES OF OPERATION



Motor drive
Electric driven



Pull cord *
Tilting of the slats
via tilt control rod



Chain drive front *
Control and tilting of slats
via chain drive, chain exit at the front



Lateral chain drive *
Control and tilting of slats
via chain drive, lateral chain exit



Lateral chain drive *
Model ISOLINE (with cover plate)
Control and tilting of slats
via chain drive, lateral chain exit



* Fabricated in accordance with the standard
for children's safety
EN 13120:2009+A1:2014 applicable
for units with cord and chain operation.

BLIND JI 25