

SELECTION

			HWISO Quattro50	HTouchCentre	HBuildingController	TouchBuco	KNX BMS	BOSS BuildingManager	
									
			Wired Systems			Bus Systems			
DESIGN	Number of motorized blinds (*1)		up to 100	up to 400	up to 800	up to 400	up to 600	beginning from 800	
	Number of wind sensors		1	2	2	2	unlimited	unlimited	
	Wind direction sensor		NO	YES	YES	YES	YES	YES	
	Number of sun sensors		2	8	8	4	4 + Sky	unlimited	
	Number of zones/areas (*2)		1	2/4	8-64	4/8	8	unlimited	
SUPREME	COMFORT	BASIC	Central and group operation	x	x	x	x	x	x
			Safety function wind	x	x	x	x	x	x
			Safety function rain/frost	x	x	x	x	x	x
			Safety function fire	x	x	x	x	x	x
			Maintenance function	x	x	x	x	x	x
			Simple sun automatic	x	x	x	x	x	x
			Simple time automatic	x	x	x	x	x	x
			Alternative operation via radio technology	x	x	x	x	x	x
	Password protection	-	x	x	x	x	x		
	Data logging	-	x	x	x	x	x		
	Extended time automatic	-	x	x	x	x	x		
	Simple energy saving function	-	x	x	x	x	x		
	Remote access via Internet	-	-	x	x	x	x		
	Communication via bus system	-	-	-	x	x	x		
	Extended sun automatic (slat-tracking)	-	-	-	x	x	x		
	Alternative operation via battery-free radio technology (EnOcean)	-	-	-	x	x	x		
	Extended energy saving function	-	-	-	x	x	x		
Integration of SMI motors	-	-	-	-	x	x			
Connection to various interfaces (KNX, LON,...)	-	-	-	-	x	x			
Optimized sun automatic (slat-tracking, shading program)	-	-	-	-	-	x			
Integration of special functions (customize)	-	-	-	-	-	x			

*1 ... The number of motorized shading does not say that the controller works only with these quantities, but indicates the best value for price

*2 ... Using multiple control units increases the number of zones / areas and sensors!